



The portable defibrillator monitor FC-1760 goes everywhere with color LCD monitor that allows ECG monitoring as required. Package is built more compact and lightweight, thereby allowing the nursing staff to use it conveniently in emergencies.

### Features

- 5.5-inch color LCD for clear information
- Optional telemetry transmitter enables both ECG and Respiration monitoring
- Voice Guidance provides the instrument status
- Built-in recorder automatically activated upon energy discharge and/or alarm
- Contact Resistance Indicator on Paddle for efficient
- Synchronous/Asynchronous mode selectable
- Rechargeable Battery or AC power operation
- Three (3) steps, one (select energy level), two (energy charge), three (discharge) for simple and quick operation

### Specification

Model		Defibrillator/Monitor, FC-1760
Size External	Wide cm	43
	Length cm	33
	Height cm	12
Display		5.5inch LCD
Recording method		Thermal dot array method
Output energy levels with 50 Ohms load		2,3,5,7,10,20,30,50,70,100,150,200,300,360joules (with external paddles) 2,3,5,7,10,20,30,50joules(with internal paddles)
Leads		I, II, III(ECG Lead), Paddle Lead, telemetry lead
Peak Voltage		5KV max ( with 100 Ohms load)
Discharge		Single-phase pulse (with 50 Ohms Load)
Power Requirements		AC 90V to 240V, 5/60Hz, 170VA Max, or 12V DC rechargeable battery